MANNOL CVT NS-3

8220

Special synthetic transmission oil for continuously variable transmissions with CVTF V-belt variator (Continuously Variable Transmission Fluid). Ensures smooth operation of automatic transmissions, guarantees minimum wear, long transmission life and fuel economy in all operating conditions and modes, with a rigid articulated chain or a steel pull chain.
Product properties:
- A unique high-viscosity synthetic base of the finest quality with a consistently high viscosity index in combination with a multifunctional additive package maintains all its properties in a wide temperature range: provides good lubricating properties at low (-45 °C and below) temperatures in winter and provides a stable oil film at extreme loads and high temperatures in summer;
- The high-tech combination of additives provides unrivalled friction stability for the belt, resulting in significant fuel savings, perfectly smooth gear changes and extended life of all transmission components through excellent lubrication properties;
- Provides excellent compatibility with seal materials, prevents them from swelling, curing and shrinking, thus reducing replacement part costs and preventing leaks;
- It has enhanced thermal and chemical stability and resistance to high-temperature thermal degradation throughout its service life. This reduces sludge, varnish, soot and other carbon deposits, significantly extends oil change intervals and ensures durability of transmission components, thereby reducing maintenance costs;
- The addition of special inhibitors effectively protects metal parts made of ferrous and non-ferrous alloys against corrosion, both when in use and when not in use;
- Effectively resists aeration, foaming and cavitation and has excellent cooling properties. It has low evaporation losses;
- Eliminates vibration and reduces noise.
CVT is specially developed for the latest generation variator JATCO CVT8 (JF016E/JF017E) used in Nissan cars - Teana, Pathfinder, Altima, Serena as well as Suzuki Landy. Suitable for variators in MITSUBISHI, RENAULT, BMW etc. cars according to the above list.
COLOUR: green.

Specifications
Approval
Recommendation
BMW 83 22 0 136 376
BMW 83 22 0 429 154
BMW EZL799
BMW EZL799A
BMW ZF CVT V1
BMW Punch EZL 799
BMW Punch EZL 799A

CHRYSLER CVTF+4
VOLKSWAGEN G 052 180
VOLKSWAGEN G 052 516
DAIHATSU AMMIX CVTF-DC
DAIHATSU AMMIX CVT-DFE
DODGE NS-2
FORD CVT23
FORD CFT30
FORD MERCON C
FORD MOTORCRAFT XT-7-QCFT
FORD WSS-M2C933-A
GM SATURN CVTF I-Green2
GM SATURN DEX-CVT
HONDA HMMF HCF-2
HONDA HMMF (Without starting clutch)
HONDA CVTF
HYUNDAI SP-CVT 1
JEEP NS-2
KIA SP-CVT 1
MAZDA CVTF 3320
MB 236.20
MB CVT28
MINI 83 22 0 136 376
MINI 83 22 0 429 154
MINI EZL799
MINI EZL799A
MINI ZF CVT V1
MINI Punch EZL 799
MINI Punch EZL 799A
MITSUBISHI DiaQueen CVTF-J1
MITSUBISHI DiaQueen CVTF-J4
MOPAR CVTF+4
NISSAN Matic W
NISSAN NS-3
NISSAN NS-2
NISSAN NS-1
AFNOR FRANCE Industrial Hydraulic Oil
RENAULT ELFMATIC
SUBARU LINEARTRONIC CVTF II
SUBARU LINEARTRONIC CVTF
SUBARU E-CVTF
SUBARU I-CVTF
SUBARU CV-30
SUZUKI CVT Fluid Green 1
SUZUKI CVT Fluid Green 2
SUZUKI CVT Fluid NS-2
SUZUKI TC
SUZUKI CVTF 3320
TOYOTA CVT Fluid TC
TOYOTA CVT Fluid FE

PACKAGING

1L	MN8220-1	Plastic	20 pcs/box
	MN8220-DR		
	MN8220-20		
	MN8220-4		
	MN8220-1ME		